

FEATURES

- Pedestrian Access Facility (Double Wing Gates)
- Plug & Play With Self Learning Capability
- Economy Stand-by Mode
- Anti-Blocking Software
- Push Open Security Software
- Adjustable Soft-Start / Soft-Stop Facility
- Intermediate Stop Position Facility
- Automatic Close / Open Safety Feature
- Adjustable Operator Speed
- Built-in Memory Retention
- Electronic Limits
- Factory Reset Function
- Error Message Display
- Connection For External Controls Such As:
 - ⇒ *Signal Light*
 - ⇒ *House Alarm*
 - ⇒ *Entry Systems Etc*



For Single-Wing Gate Up To 200kg

To Suit:

- Wing Width / Height Max 2.5m / 2.5m
- Wing Weight Max 200kg
- Max. 50% Covered Wing Surface

Complete With:

- One Comfort 515 Operator
- One Control x.51 Panel
- One Digital 304 Transmitters
- Fittings, Gate & Post Brackets and Mounting Material



For Double-Wing Gates Up To 200kg Per Wing

To Suit:

- Wing Width / Height Max 2.5m / 2.5m
- Wing Weight Max 200kg
- Max. 50% Covered Wing Surface

Complete With:

- Two Comfort 515 Operators
- One Control x.51 Panel
- One Digital 304 Transmitters
- Fittings, Gate & Post Brackets and Mounting Material



For Single-Wing Gate Up To 400kg

To Suit:

- Wing Width / Height Max 3.0m / 2.5m
- Wing Weight Max 400kg
- Max. 50% Covered Wing Surface

Complete With:

- One Comfort 520 Operator
- One Control x.51 Panel
- One Digital 304 Transmitters
- Fittings, Gate & Post Brackets and Mounting Material



For Double-Wing Gates Up To 400kg Per Wing

To Suit:

- Wing Width / Height Max 3.0m / 2.5m Per Wing
- Wing Weight Max 400kg Per Wing
- Max. 50% Covered Wing Surface

Complete With:

- Two Comfort 520 Operators
- One Control x.51 Panel
- One Digital 304 Transmitters
- Fittings, Gate & Post Brackets and Mounting Material



Available For Single-Wing & Double Wing Gates

To Suit:

- Wing Width / Height Max 4.0m x 2.5m Per Wing
- Wing Weight Max 400kg Per Wing
- Max. 50% Covered Wing Surface

Complete With:

- One or Two Comfort 520L Operators
- One Control x.51 Panel
- One Digital 304 Transmitters
- Fittings, Gate & Post Brackets and Mounting Material

TECHNICAL SPECIFICATIONS

Operator	515	520	520 L
Push Pull Force	1000N	1500N	1500N
Door Travel Speed	15 - 20mm/Sec	15 - 20mm/Sec	15 - 20mm/Sec
Approx. Opening Time	15 - 25 Sec	15 - 25 Sec	20 - 30 Sec
Normal Voltage	230V / 50Hz	230V / 50Hz	230V / 50Hz
Control Voltage	24V DC	24V DC	24V DC
Radio Frequency	868 MHz	868 MHz	868 MHz
Ampage	1.0 A	1.0 A	1.0 A
Watts	0.2 Kw	0.2 Kw	0.2 Kw