

In Ground Swing Gate Kits

Include Ram/s, Controls, Receiver, 2 x Transmitters & Photocell

Please consult our sales department for all available access control options

	Max Wing Weight & Length	Opening Time to 90°	Double Kit Code	Single Kit Code	Panel
DU.IT14 DOMESTIC USE 110° standard opening.	500Kg @ 3M	20s	DU.3R	DU.3R/1	DA.Brain
DU.350 INTENSIVE USE 110° standard opening.	500Kg @ 4M	18s	DU.3C	DU.3C/1	DA.Brain
DU.350VN INTENSIVE USE Fast version 110° standard opening.	500Kg @ 3M	11s	DU.4C	DU.4C/1	DA.Brain



DU.IT14 Residential



DU.350N Intensive

	Product Description
DU.IT180N	180° Release device to suit DU.IT14 Swing Gate Operator (One required per operator) Max Wing Width 2.5M
DU.180N	180° Release device to suit DU.350 Swing Gate Operator (One required per operator) Max Wing Width 2.5M
DU.FCN	Mechanical limit switch to suit DU.IT14 Swing Gate Operator (One required per operator).
DU.V90	12V Horizontal & Vertical Electric Lock c/w counterplate
DU.V96	12V Vertical Electric Lock c/w counterplate
97-GL1200NTB	1200NM Maglock (Including 03-320 PSU & 03-270 Relay)
DA.HEAD	230V Control Panel with Built-in Receiver
DA.BRAIN	230V Multi-Function Control Panel (Plug-in receiver required - see back page)
Brackets	Weld On Brackets supplied with Swing Gate Ram Kits Bolt On Available for Timber gates on request