

SAFETY ACCESSORIES

PHOTOCELLS



LS22



FT42



FT42B

MODELS

CODE	DESCRIPTION
178 435	LS22 Pair of photocells for external use, fitting for posts CH-51N and CH-101N
178 436	FT42 Pair of photocells for external use, adjustable by 180°
178 437	FT42B Pair of photocells for external use, adjustable by 180°, battery-powered

TECHNICAL SPECIFICATIONS

		LS22	FT42	FT42B
ELECTRICAL DATA				
Power	V AC	12-24	12-24	12-24
	V DC	12-35	12-35	12-35
Range	m	25	25	20
Consumption Rx	mA	27	27	35
Consumption Tx	mA	10	10	0,04
Relay contacts max. supply	A	1	1	1
GENERIC DATA				
Protection class	IP	54	54	54
Dimensions (L - W - H)	mm	30 - 28 - 90	35 - 35 - 110	35 - 35 - 110
Operating temperature	°C	-20° to +55°	-20° to +55°	-20° to +55°

SAFETY ACCESSORIES

POSTS FOR PHOTOCELLS



CH-51N

CH-101N

MODELS

CODE	DESCRIPTION
178 438	CH-51N Pair of support posts H 50 cm, anodized aluminum
178 439	CH-101N Pair of support posts H 100 cm, anodized aluminum

FITTING ACCESSORIES



LS22

Pair of photocells for external use

178 435



Special 630

Pair of photocells for use in pillars CH

88 176